

Modelling Reactive Systems

- Interaction with the environment: reactive to *events*.
- Autonomous behaviour: *timeouts*.
- Describe system with *modes* (hierarchical) and *concurrent* units.
- Use programming language + threads and timeouts (OS)?




“Nontrivial software written with threads, semaphores, and mutexes are incomprehensible to humans”¹


Programming language (and OS) is too low-level
-> most appropriate formalism: “what” vs. “how”

¹E. A. Lee, "The problem with threads," in *Computer*, vol. 39, no. 5, pp. 33-42, May 2006.

Running Example




Workflow



³ Hans Vangheluwe and Ghislain C. Vansteenkiste. A multi-paradigm modeling and simulation methodology: Formalisms and languages. In European Simulation Symposium (ESS), pages 168-172. Society for Computer Simulation International (SCS), October 1996. Genoa, Italy.

⁴ FTG+PM: An Integrated Framework for Investigating Model Transformation Chains, Levi Lúcio, Sadaf Mustafiz, Joachim Denil, Hans Vangheluwe, Maris Jukss. System Design Languages Forum (SDL) 2013, Montreal, Quebec. LNCS Volume 7916, pp 182-202, 2013.

States



- R1: Three differently colored lights: red, green, yellow.
- R2: At most one light is on at any point in time.


(Simulated) Plant




Environment



<<observe>>



Default State



- R1: Three differently colored lights: red, green, yellow.
- R2: At most one light is on at any point in time.
- R3: Initially, the red light is on.


(Simulated) Plant





Environment



<<observe>>



Transitions



- R1: Three differently colored lights: red, green, yellow.
- R2: At most one light is on at any point in time.
- R3: Initially, the red light is on.
- R4: Cycles through red on, green on, and yellow on.
- R5: Duration: Red -> 5s, Green -> 3s, Yellow -> 2s

event(params) [guard] / output_action(params)

(Simulated) Plant





Environment



<<observe>>



{R: on, Y: off, G: off}
{R: off, Y: on, G: on}
{R: off, Y: on, G: off}

Yakindu¹: Modelling





⁵ <https://www.itemis.com/en/yakindu/state-machine/>

Yakindu: Simulation




Hierarchy


- R6: Police can interrupt autonomous operation.
 - Result = blinking yellow light (on -> 1s, off -> 1s).
- R7: Police can resume an interrupted traffic light.




Semantics/Meaning?
 FLATTEN



History




- R7: Police can resume an interrupted traffic light.
 - Result = light which was on at time of interrupt is turned on again.




- (H) *shallow history*
- (H*) *deep history*



Concurrency




Semantics/Meaning?



Statecharts Testing (White-Box)




Code Generation



interrupts

events



Interface:

- setRed(boolean)
- setGreen(boolean)
- setYellow(boolean)

Interface:

- in event *police*